

NEW











Set up

Specifications

•	
Operating environment	Indoors, pollution degree 2, operable at an altitude specified in specifications of each measuring instrument to which the adapter is attached
Operating temperature and humidity (Storage temperature and humidity)	-30°C (-22°F) to 70°C (158°F) 90% RH or less (no condensation)
Standards	Safety: EN61010, RF: EN300 328, RF EMC: EN301 489-1, EN301 489-17, Exposure: EN62479
Maximum attaching/	5000 times

GENNECT Cross App Confirmed compatible OSs	iOS 13 or later, Android 8 or later, Bluetooth® 4.0 or later
Bluetooth® Communication distance	About 10 m (line-of-sight distance)
Product warranty period	3 years (except for the connector)
Dimensions and Mass	Approx. $16.4 \text{mmW} \times 6.7 \text{mmH} \times 15.6 \text{mmD} (0.65'' \text{W} \times 0.26'' \text{H} \times 0.61'' \text{D}), \text{Approx. } 1.5 \text{ g} (0.05 \text{ oz.})$
Accessory	Instruction manual

Model



Model: WIRELESS ADAPTER Z3210

Model No. (Order code): Z3210

Compatible products (scheduled included)



WIRELESS ADAPTER Z3210

web site



For more information on supported regions and products, please visit this dedicated site.

More compatible HIOKI products and apps are on their way

Downloading GENNECT Cross



GENNECT Cross is a free app. Downloaded it to your tablet or smartphone from Google Play™ or App Store™. Simply search for "HIOKI" and GENNECT Cross download "GENNECT Cross" today!









 $Note: Company\ names\ and\ product\ names\ appearing\ in\ this\ catalog\ are\ trademarks\ or\ registered\ trademarks\ of\ various\ companies.$ *The Bluetooth* word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by HIOKI E.E. CORPORATION is under license.

DISTRIBUTED BY



HEADQUARTERS

81 Koizumi. Ueda, Nagano 386-1192 Japan https://www.hioki.com/



Scan for all regional contact information